

Dispersant Tech-5320

Description

Tech-5320 is a polymeric dispersant suitable for organic pigment especially dispersion in medium polarity solvent borne and UV coating systems. It has good compatibility with many kinds of resin, suitable for all kinds of pigment and filler, and with strong dispersing power and excellent store stability.

Physics and Chemical properties

Ingredient: Block copolymer of macromolecular with acidic groups

Appearance: Waxy solid (gradually turns into viscous liquid above 45 degrees)

Content: 100%

Specialty

1. Tech-5320 dispersant suitable for all kinds of pigment dispersion in medium polarity solvent borne coating systems, especially for organic pigment such as **HPP** and with good compatibility.
2. Tech-5320 is polymeric dispersant with strong dispersing power and excellent store stability.
3. Tech-5320 dispersant suitable for those organic pigments hard to disperse in high solid content because of it could decrease the viscosity effectively.

Application System and Dosage

Tech-5320 is recommended to use in medium polarity solvent borne and UV coating systems.

Usually, it should be charged before the grind stage during the produce, with **10%** to **15%** to inorganic pigment, **5%** to **6%** to TiO₂, **30%** to **50%** dosage to organic pigment, **50%** to **100%** to carbon black.

Package

25kg metal pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■Shanghai Company –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■Guangdong Company –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

