

Dispersant Tech-5044

Description

Tech-5044 is a dispersant special designed for putty. It has excellent wetting ability for inorganic pigments and could decrease the viscosity.

Physics and Chemical properties

Ingredient: Polycarboxylic acid amine salt

Appearance: Yellow transparent liquid

Content: 50%

Solvent: mixed dibasic esters

Specialty

1. Tech-5044 is suitable for middle-polar systems and has excellent compatibility with many kinds of resins.
2. Tech-5044 could decrease the mill viscosity and it could increase the pigment content in the color paste.

Application System and Dosage

Tech-5044 is recommended to use in solvent borne coating systems.

Usually, it should be charged before the grind stage during the produce, with **1%** to **2%** to inorganic pigment, with **5%** to **20%** to *bentonite*.

Package

25kg plastic pail

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■Shanghai Company –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■Guangdong Company –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

