

Dispersant Tech-6731

Description

Tech-6731 is a polymeric dispersant designed suitable for both organic pigment and inorganic pigment. It could decrease the viscosity rapidly with low foaming, meanwhile, increase the paint film gross.

Physics and Chemical properties

Ingredient: Copolymer with pigment unique affinity group

Appearance: yellow transparent liquid

Content: 25%

Solvent: water

Specialty

1. Tech-6731 dispersant suitable for inorganic pigment dispersion in water borne coating systems.
2. Tech-6731 dispersant has no reverse effect on the water-resistance of the paint film.

Application System and Dosage

Tech-6731 is recommended to use in water borne coating systems.

Usually, it should be charged before the grind stage during the produce, with **50%** to **10%** dosage to inorganic pigment

Package

25kg plastic pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■Shanghai Company –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■Guangdong Company –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

