

Dispersant Tech-6191

Description

Tech-6191 is a polymeric dispersant designed suitable for both organic pigment and inorganic pigments in waterborne system. It could decrease the viscosity with low foaming, meanwhile, increase the paint film gross.

Physics and Chemical properties

Ingredient: Copolymer with pigment unique affinity group

Appearance: Yellow viscous liquid

Content: 100%

Specialty

1. Tech-6191 dispersant suitable for organic pigment dispersion in water borne coating systems.
2. Tech-6191 is a polymeric dispersant so that could make the system low foaming.
3. Tech-6191 dispersant suitable for those organic pigments hard to disperse in high solid content

Application System and Dosage

Tech-6191 is recommended to use in water borne coating systems.

Usually, it should be charged before the grind stage during the produce, with **20%** to **50%** dosage to organic pigment quality, 20% to 50% dosage to carbon black.

Package

25kg plastic pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company** –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company** –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

